



## Data Sheet

### T2.8 SELF BUNDED TANK FOR MINOR STORAGE

DTE Self banded **Wraptank™** storage tank eliminates the need for complex bunding requirements and offers maximum cost effectiveness and versatility.



### STANDARD FEATURES

- Suitable for Petroleum, Petrochemical and Chemical application
- Designed and manufactured in accordance with
  - AS 1940 – 2004 The storage & handling of flammable & combustible liquids, section 2, Minor storage
  - AS 1692 – 2006 Tanks for flammable & combustible liquids
- Overall dimensions: 1700mm long x 1700mm wide x 1100mm high
- Tare weight 1100kg (empty)
- Safe fill level – 2500 litres
- Interstitial space monitored by dipstick
- Lockable spill containment box on top of tank containing manway and monitoring pipe.

**Perth – Head Office**  
 11 Erceg Road Yangebup  
 Western Australia 6164  
 Phone: (08) 9418 8566  
 Fax: (08) 9418 8544

**Queensland**  
 7-511 Olsen Avenue Southport  
 Queensland 4215  
 Phone: (07) 5539 6622  
 Fax: (07) 5539 6522

**New South Wales**  
 11-354 Bay Street Brighton Le Sands  
 New South Wales  
 Phone: (02) 9599 0266  
 Fax: (02) 9599 0288



## Diverse Tank Engineering

- Manway complete with inspection hatch, 50mm dip point and dipstick, 50mm fill pipe for filling by auto shut off nozzle and pressure & vacuum vent (**Optional**)
- 50nb suction
- 25nb return line
- 50mm vent pipe, c/w lockable mounting bracket for transportation of vent pipe
- Fork lift pockets and crane lifting lugs
- Tanks able to be stacked (empty only)
- Painted – class 2 ½ blast clean followed by two pack epoxy top coat
- Signage as per AS1940-2004
- Also available in 1,500 litres (SFL) and 2,500 litres (SFL) size



**Perth – Head Office**  
 11 Erceg Road Yangebup  
 Western Australia 6164  
 Phone: **(08) 9418 8566**  
 Fax: **(08) 9418 8544**

**Queensland**  
 7-511 Olsen Avenue Southport  
 Queensland 4215  
 Phone: **(07) 5539 6622**  
 Fax: **(07) 5539 6522**

**New South Wales**  
 11-354 Bay Street Brighton Le Sands  
 New South Wales  
 Phone: **(02) 9599 0266**  
 Fax: **(02) 9599 0288**